

Universal High Flow Automatic Coupling

ZSi-Foster announces the latest in pneumatic style products.



Works with all ¹/₄" body size Industrial, Tru-Flate, ARO, CEJN 320 (European Interchange), Parker Rectus 25/26, Eaton Hansen Auto Flow 24, Prevost ERP, and Coilhose Euro/Mega high flow plugs.

- High-flow valve design provides 20% flow increase over standard spade-valved ¹/₄" body size sockets
- Couples with other common plug profiles making it easy to interchange with your existing plugs
- Offers automatic push-to-connect operation
- All brass design for the sockets
- Made in the U.S.A.

Call ZSi-Foster at (866) 918-3003 or order now at ZSi-Foster.com





Universal High Flow Automatic Coupling

Maximum PSIG: 300 psig (20.7 bar) Media: Compressed Air Seal Material: Buna-N Temperature Range: -40° to 225°F (-40° to 107°C) **Body Material: Brass** Number of Pawls: 6











UHF3103

UHF3003

ARO 210 European Interchange High Flow

Series 3



	Part No.	Item	Thread	Interchange	Body Size	Hex	Length	O.D.	Weight (lbs)
	UHF3003	Socket	¹ ⁄4" Female NPT	Industrial, ARO, TruFlate and Euro- pean	1⁄4"	19mm	2.20"	1.00"	0.269
	UHF3103		¹ ⁄4" Male NPT				2.28"		0.238
	EHF10	Plug	¹ ⁄4" Male NPT	CEJN 320	1⁄4"	⁹ ⁄16"	1.51	0.562	0.044
	EHF11		¹ ⁄4" Female NPT			5⁄8"	1.38	0.625	0.045
	EHF14		³ ⁄8" Male NPT			¹¹ ⁄16"	1.625	0.687	0.077
	EHF15		³∕₅" Female NPT			7⁄8"	1.5	0.875	0.096
	EHF17		³∕₃" Hose Barb			-	2.06	0.562	0.047

Why Should You Buy?

- One socket that will connect to multiple plugs; potentially eliminating the need for multiple sockets (cost savings)
- Automatic push-to-connect operation which allows one handed connection (ease-of-use)
- Require the highest possible flow (superior performance)
- Made in the U.S.A. (highest quality standards)

Call ZSi-Foster at (866) 918-3003 or order now at ZSi-Foster.com

ZSi-Foster



Canton, MI | La Mirada, CA | Ocala, FL | Springfield, MO © Copyright 2020 ZSi-Foster / Printed & Designed in the USA / 3.20 / UHF-2