

BETA Hydraulic Clamps™



Beta Cushions Now Made in the USA



- Polypropylene Cushion and Steel Components
- Temperature range is
 -22°F to 194°F (-30°C to +90°C)
- Shock-Absorption, Vibration Dampening and Noise Reducing Properties
- Hydraulic Hoses, Pipes, Tubes and Electrical Cables

Installation Options For All Your Application Needs!



Weld

Mounted

F



Rail Mounted

Channel Mounted

Call ZSi-Foster at (800) 323-7053 or order now at ZSi-Foster.com

ZSi-Foster Canton, MI | La Mirada, CA | Ocala, FL | Springfield, MO



BETA Hydraulic Clamps™



Beta Standard Series

- For standard hydraulics and systems with less than 1500 PSI without dynamic loads
- · Polypropylene cushion and steel components



Beta Standard Smoothie Series

- Reduces wear on hose connection caused by vibration and surge.
- Chamfered and smooth core protects hose cover and extends hose life.
- Uses Beta Standard hardware
- Polypropylene cushion & steel components



Aluminum Beta

 Aluminum cushions with steel components are used in high heat applications up to 500°F



Beta Twin Series

- For standard hydraulics, general pipe construction and electrical cables
- Polypropylene cushion and steel components



Beta Twin Smoothie Series

- Reduces wear on hose connection caused by vibration and surge.
- Chamfered and smooth core protects hose cover and extends hose life.
- Uses Beta Twin hardware
- Polypropylene cushion and steel components



Stainless Steel Beta

- Lower and upper plates: stainless steel type 304
- Screw bolts: steel, S40C, stainless steel type 304
- Stainless steel hardware with polypropylene cushion are used in applications where external corrosion is a concern.



Beta Heavy Series

- For systems with greater than 1500 PSI operating pressure, operations with pressure surges, and applications with wide temperature fluctuations.
- Absorbs high levels of shock, noise, and vibration
- Polypropylene cushion & steel components



Beta Rubber Inserts Series

- Available in standard and heavy
- One cushion block provides flexible size range of cushioning.
- Smooth bore core can be used on hose, or for vibration reduction



Beta Adapter Series

- Allows a clamping junction to be inserted into hydraulic lines
- The adapter body is offered in two sizes for use with the Z-Clamp adapter inserts

Call ZSi-Foster at (800) 323-7053 or order now at ZSi-Foster.com

ZSi-Foster - Canton, MI | La Mirada, CA | Ocala, FL | Springfield, MO

© Copyright 2019 ZSi-Foster / Printed & Designed in the USA / 09.19 / Bete-2-page-1