

FVEP Screw Couplings for High Pressure Applications



Connect and Disconnect with up to 5,075 psi Residual Pressure



- Zinc Nickel Plated Carbon Steel
- Rated for 1,200 Hours
 Protection Against White and
 Red Rust
- Large body size ½" to 1-1/4"
- Operating temperatures with Nitrile Seals: -40°F to 223°F

- Screw Thread Connection Eliminates Brinelling
- Orange Seal for Proper Connection Verification
- Socket Sleeve can be Pushed Back for Access to the Mating Face
- Flat Face Design Prevents Fluid Loss During Disconnection



Call ZSi-Foster at (866) 918-3003 or order now at ZSi-Foster.com



FVEP Screw Couplings for High Pressure Applications



Mobile Hydraulic Equipment OEMs & Aftermarket



Part No.	Туре	Finish	Body Size	Thread Size	Max. Working Pressure Psi	Socket Burst Pressure Psi	Plug Burst Pressure Psi	Combined Burst Pressure Psi	Weight Each (lbs)
FVEP-08S-08	Socket	Zinc Nickel Plated Carbon Steel	1/2"	½" Female NPT	7,975	14,500	20,300	20,300	1.2
FVEP-08P-08	Plug								1.3
FVEP-12S-12	Socket	Zinc Nickel Plated Carbon Steel	3/4"	³ / ₄ " Female NPT	7,975	14,500	20,300	20,300	1.7
FVEP-12P-12	Plug								1.5
FVEP-12S-12ORB	Socket			1- ¹ / ₁₆ "-12 Female ORB					1.6
FVEP-12P-12ORB	Plug								1.4
FVEP-16S-12	Socket	Zinc Nickel Plated Carbon Steel	1"	3/4" Female NPT	7,250	15,225	20,300	20,300	2.5
FVEP-16P-12	Plug			/4 Female NFT					2.3
FVEP-16S-12ORB	Socket			1- ¹ / ₁₆ "-12 Female ORB					2.5
FVEP-16P-12ORB	Plug								2.3
FVEP-16S-16	Socket			1" Female NPT					2.4
FVEP-16P-16	Plug								2.3
FVEP-16S-16ORB	Socket			1-5/16"-12 Female ORB					2.4
FVEP-16P-16ORB	Plug			1-716 -12 Female OND					2.2
FVEP-20S-20	Socket	Zinc Nickel Plated Carbon Steel	1-1/4"	1- ¹ / ₄ " Female NPT	6,815	14,500	18,850	18,850	3.8
FVEP-20P-20	Plug								3.2
FVEP-20S-20ORB	Socket			1-5/8"-12 Female ORB					3.8
FVEP-20P-20ORB	Plug								3.2

Call ZSi-Foster at (866) 918-3003 or order now at ZSi-Foster.com

ZSi-Foster

Canton, MI | La Mirada, CA | Ocala, FL | Springfield, MO

